

Architectural ACCESS DOOR



The Nystrom Architectural Access Door is built with the architect in mind. Constructed with an industry-standard steel door, the updated design further improves on strength and aesthetics.

FEATURES

ANTI-FLEX FRAME Fasteners are inserted through our patent-pending Easy Install Tabs, firmly fitting the door to the wall without flexing the frame.

PAINLESS INSTALLATION When fasteners are not required, quickly and easily install your new panel by bending our patent-pending Easy Install Tabs over the drywall.

OPTIONAL STAINLESS STEEL The spot free design on the face of the door gives an aesthetically pleasing appearance.

DETAILS

DOOR

- NT/NW: 16 gauge Steel
- NP: 14 gauge Steel
- 16 gauge Stainless Steel, Type 304

FRAME

- 16 gauge Steel
- 16 gauge Stainless Steel, Type 304

SIZE

- Min: 6 inches by 6 inches
- Max: 24 inches by 72 inches or 48 inches by 48 inches

INSTALLATION Ceiling or Wall

FLANGE 1 inch Exposed, Drywall Bead or Plaster Bead

HINGE Concealed Spring Button

PAN DEPTH 1/2 inch

FINISH White Powder Coat (Steel) or #4 Satin (Stainless Steel)

MATERIALS



White
Powder Coat



#4 Satin
Stainless Steel


FLANGES



1 inch Flange



Drywall Bead



Plaster Bead

LATCHES



Screwdriver
Cam Latch



Key Operated
Cam Lock



Mortise
Lock Prep



Knurled
Knob

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
N				X		
	T 1 inch Flange W Drywall Bead P Plaster Bead	C Screwdriver Cam Latch L Key operated Cam Lock M Mortise Lock (1-1/8") Prep N Knurled Knob	Standard Sizes (W x L) 6" x 6" 16" x 20" 24" x 36" 8" x 8" 18" x 18" 24" x 48" 10" x 10" 18" x 24" 30" x 30" 12" x 12" 20" x 30" 30" x 36" 12" x 18" 22" x 22" 32" x 32" 12" x 24" 22" x 30" 36" x 36" 14" x 14" 24" x 24" 16" x 16" 24" x 30"	B Galvannealed D14 14 gauge Steel Door G Gasketing M Masonry Anchors L Louvered Door S Stainless Steel, Type 304		

Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.