


ALUMINUM I-BEAM MOUNTING BRACKET

(A068FCLR)



NOTES:

В

1. MATERIAL: 6063-T5 ALUMINUM

2. FINISH: CLEAR ANODIZED

③ 1/4"-20 x 1" PHILLIPS FLAT HEAD STAINLESS STEEL SCREW (14201PFMS188) WITH LOCK NUT (1420NLN188), INCLUDED.

4" ALUMINUM

CRASH RAIL

(A053CLR)/

4. PROVIDED IN 12' CONTINUOUS LENGTHS, TO BE FIELD CUT AND DRILLED.

BACK-UP CHANNEL.

BY OTHERS.

- 5. RETURNS AND CORNERS: PRE CUT AND DRILLED FOR FIELD INSTALLATION. END CAP: #CRAE4-BI2-EC, OUTSIDE CORNER: #CRAE4-BI2-OC, INSIDE CORNER: #CRAE4-BI2-IC
- 6. PARTITION COMPONENTS BY OTHERS.

PROJECT: ARCHITECT: CONTRACTOR: 4" ALUMINUM CRASH RAIL, EXTENDED, 2" I BEAM BRACKET, CLEAR ANODIZED FINISH 9300 73rd Avenue North Minneapolis, MN 55428 NAME DATE SIZE DWG. NO. REV Α CRAE4-BI2 Α DRAWN DKL 11/25/13 RELEASED | PGE |11/25/13| WEIGHT: 1.7 LB/LF SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

2