



QUANTITY

COLOR



NOTES:

1. **PROFILE:** HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.078" (1.98mm) THICK
2. CLASS A FIRE RATING, TESTED TO ASTM E84
3. **RETAINER:** CONTINUOUS 6063 T-5 ALUMINUM RETAINER, NOMINAL 0.062" (1.57mm) THICK
4. **EXTRUSION:** PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL AGENT
5. **VINYL CRASH RAIL LENGTH:** PROVIDED IN 20' CONTINUOUS SECTIONS
6. END CAP: #CRVS4C-EC, OUTSIDE CORNER: #CRVS4C-OC, 135 DEG OUTSIDE CORNER: #CRVS4C-OC135, INSIDE CORNER: #CRVS4C-IC, SPLICE KIT; #CRVS4C-SK
7. FASTENERS AND PARTITION COMPONENTS PROVIDED BY OTHERS.

PROJECT:			
ARCHITECT:			
CONTRACTOR:			
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE: 4" VINYL CRASH RAIL ACCENT STRIP SURFACE MOUNT, CONTINUOUS RETAINER	
NAME	DATE	SIZE	DWG. NO.
DRAWN	MDS 23APR13	A	CRVS4C-AS
RELEASED	PGE 01MAY13	WEIGHT: 1.03 lbs/ft	SHEET 1 OF 1