


QUANTITY
COLOR

**NOTES:**

- PROFILE:** HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.078" (1.98mm) THICK
- CLASS A FIRE RATING,** TESTED TO ASTM E84
- RETAINER:** CONTINUOUS 6063 T-5 ALUMINUM RETAINER, NOMINAL 0.062" (1.57mm) THICK
- EXTRUSION:** PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL AGENT
- VINYL CRASH RAIL LENGTH:** PROVIDED IN 20' CONTINUOUS SECTIONS
- END CAP:** #CRVS4C-EC, **OUTSIDE CORNER:** #CRVS4C-OC, **135 DEG OUTSIDE CORNER:** #CRVS4C-OC135, **INSIDE CORNER:** #CRVS4C-IC, **SPLICE KIT:** #CRVS4C-SK
- FASTENERS AND PARTITION COMPONENTS PROVIDED BY OTHERS.**

PROJECT:				
ARCHITECT:				
CONTRACTOR:				
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE: 4" VINYL CRASH RAIL SURFACE MOUNT CONTINUOUS RETAINER		
NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	MDS 23APR13	A	CRVS4C	A
RELEASED	PGE 01MAY13	WEIGHT: 1.03 lbs/ft	SHEET 1 OF 1	

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.