

EM-SREADL-8X9 (Shown) Running Man Exit Arrow Down Left

Specification:

Egress Marking - Photoluminescent Sign High Performance, Safety Grade, Rigid Sheet

Thickness: .051 inch

Sel-Adhesive Tabs Included

Luminous Compliance: ASTM E 2072, NYC RS6-1, UL 1994 Listed

Model	Description			
EM-SREAR-8X9	Running Man Exit Arrow Right			
EM-SREAUR-8X9	Running Man Exit Arrow Up Right			
EM-SREADR-8X9	Running Man Exit Arrow Down Right			
EM-SREAL-8X9	Running Man Exit Arrow Left			
EM-SREAUL-8X9	Running Man Exit Arrow Up Left			
EM-SREADL-8X9	Running Man Exit Arrow Down Left			

EM-SREA_8X9

Egress Marking, Safe-T-Lume, Photoluminescent Sign, Running Man, Exit, Arrow _, 8" X 9", Adhesive Tab

2

		9300 73rd Avenue North Minneapolis, MN 55428			Running Man, Exit, Arrow _, 8" 2	
		NAME	DATE	SIZE	DWG. NO.	
ROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE	DRAWN	DKL	3/6/19	Α	EM-SREA_8X9	
THOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.	RELEASED	BB	3/6/19	WEI	WEIGHT:	
_						

REV Α

SHEET 1 OF 1

nystrom