
Detention + Institution Cabinets



Nystrom's Detention Series Cabinets provide the specifier with a substantial unitized design in 12 gauge cold rolled steel construction for maximum security facilities. All corners are mitered and ground smooth to eliminate any dangerous projections. The heavy-duty continuous hinge adds to the secure features of these cabinets.



Hose DETENTION CABINETS

DOOR 12 gauge Cold Rolled Steel

MOUNTING Recessed or Surface

OPTIONS Lock Prep, Lettering, Fire-Rated (2-hour), Polyester Finish



HOSE CABINET

П	MODEL	WALL	CAPACITY	BOX I.D.			FRAME O.D.		WALL OPENING			Ġ	()
1	MODEL	MOUNTING						0				ADA	FRC
	DC-1002	Recessed	100' Hose	24	30		27-3/4			31	6	Yes	Yes
	DC-1052	Surface	Unit	24	30	5-1/2	-	-	-	-	-	No	No

HOSE AND EXTINGUISHER CABINET

MODEL	WALL MOUNTING	CAPACITY	K	BOX I.D. L	М	FRAMI N	E O.D. O		NING D	اج ADA	∅ FRC
DC-1302	Recessed		30	30	8	33-3/4	33-3/4		8-1/2		Yes
DC-1352	Surface	2-1/2 gal Water Ext.	30	30	8	-	-	-	-	No	No

Extinguisher DETENTION CABINETS



DOOR 12 gauge Cold Rolled Steel

MOUNTING Recessed or Surface

OPTIONS Lock Prep, Lettering, Fire-Rated (2-hour), Polyester Finish

MODEL	WALL	WALL CAPACITY		BOX I.D.		FRAM	WALL OPENING			Ġ.	٨	
MODEL	MOUNTING										ADA	FRC
DC-1704	Recessed	10 Lb. Dry Chem. Ext.	9	24	8	12-3/4	27-3/4	10	25	8-1/2	Yes	Yes
DC-1706	Recessed	2-1/2 gal. Water Ext.	12				30-3/4		28	8-1/2	Yes	Yes
DC-1754	Surface	10 Lb. Dry Chem. Ext.	9	24	8	-	-	-	-	-	No	No
DC-1756	Surface	2-1/2 gal. Water Ext.	12	27	8	-	_	-	-	-	No	No