

Insulated Fire-Rated ACCESS DOOR

Designed for wall and ceiling applications, this fire-rated Insulated Access Door is UL and Warnock-Hersey listed. Engineered with mineral fiber to assist in reducing heat transfer in the event of a fire.

FEATURES

FIRE-RATED Independently tested and labeled for 1-1/2 hours for wall applications and 3 hours for ceiling applications.

EASY OPERATION This self-closing door features an inside knurled knob latch release is easy to operate.

CUSTOM SIZING Custom sizes available from 6 inches by 6 inches to 48 inches by 48 inches.



DETAILS

DOOR 20 gauge Steel, Self-Closing

FRAME 16 gauge Steel

SIZE

- Min: 6 inches by 6 inches
- IT Max: 24 inches by 72 inches or 48 inches by 48 inches
- IW/IP Max: 36 inches by 48 inches

INSTALLATION Ceiling or Wall

HINGE

- IT: Flush Continuous Piano
- IW/IP: Concealed Pin

FINISH White Powder Coat

INSULATION 2 inch Thick, Fire-Rated Mineral Fiber, R-8

CERTIFICATION

- UL listed "B" label for 1-1/2 hours (Wall)
- Warnock-Hersey listed for 3 hours (Ceiling)

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
I				X		
	T 1 inch Flange W Drywall Bead P Plaster Bead	K Knurled Knob / Key Operated Latch Bolt M Mortise Lock (1-1/8") Prep	Standard Sizes (W x L) 8" x 8" 18" x 24" 24" x 48" 10" x 10" 20" x 30" 30" x 30" 12" x 12" 22" x 22" 32" x 32" 12" x 18" 22" x 30" 36" x 36" 12" x 24" 22" x 36" 36" x 48" 14" x 14" 24" x 24" 48" x 48" 16" x 16" 24" x 30" 18" x 18" 24" x 36"	B Galvannealed G Gasketing M Masonry Anchors S Stainless Steel, Type 304		

Rough opening is door size + 1/2 inch minimum. Additional sizes available, call for more information.
*Wall application only.

MATERIALS



White
Powder Coat


FLANGES



1 inch Flange



Drywall Bead



Plaster Bead

LATCHES



Knurled
Knob



Mortise
Lock Prep