





CURB FLASHING SECTION B-B " 3.45" LENGTH MOUNTING FLANGE

SPECIFICATIONS:

- $\fbox{)}$ COVER: 11 GA (0.090") ALUM COVER STIFFENED TO WITHSTAND A LIVE LOAD OF 40PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN
- (2) **LINER:** 18 GA (0.04") ALUM
- $\boxed{3}$ CURB: 11 GA (0.09") ALUM, CURB COUNTERFLASH WITH EZ TABS
- 4 FINISH: MILL
- (5) HINGE: PINTLE HINGE WITH STAINLESS STEEL HINGE
- (§) SPRING: GAS SPRING WITH DAMPER FOR SMOOTH, CONTROLLED COUNTERBALANCED LIFT ASSIST
- ⟨7⟩ HOLD OPEN ARM: STEEL AUTOMATIC HOLD OPEN ARM LOCKS COVER IN FULLY OPENED POSITION WITH RED GRIP HANDLE RELEASE

- $\ensuremath{\langle 8 \rangle}$ LATCH: SINGLE POINT LATCH HOLDS COVER CLOSED AGAINST 20 PSF WIND UPLIFT. EXTERNAL PALM RELEASE, INTERNAL RELEASE HANDLE WITH PADLOCK HASP
- $\overline{\langle 9 \rangle}$ INSULATION: 1" FIBERGLASS IN COVER, 1" POLYISO (R6) IN CURB
- (10) GASKET: ADHESIVE-BACKED EPDM RUBBER EXTRUSION
- (11) PULL HANDLE: INTERIOR PULL DOWN HANDLE
- 12 DOME:

ROOF HATCH SIZE: "(WIDTH) x "(LENGTH)

OPTIONS

Stainless Steel Hardware

Double Wall Curb

		PROJE(CT:				
	ARCHITECT:						
	CONTRACTOR:						
	QTY:						
		PART:	#:				
▶ ¶ nystrom°				'n	TITLE:		
	9300 73rd Avenue North Minneapolis, MN 55428						
		NAME	DATE	SIZE	DWG. NO.		REV
	DRAWN			Α	Generic Nystrom RH RHLA_X_S_F	ShpDr	-
	RELEASED			WE	IGHT:	SHEET 1 (OF 2

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED. ©2020 NYSTROM

2

1

