Safe-T-Lume[™]

EGRESS TAPE

The Safe-T-Lume Egress Tape is a photoluminescent acrylic tape which provides a cost effective option for marking egress paths. It is manufactured from 16 mil acrylic and is easy to install and clean. The material has been tested to UL 1994 and ASTM E2073 test standards and meets current IBC, IFC, and NFPA code requirements.




SAFE EGRESS The glow-in-the-dark photoluminescent tape provides needed illumination for a safe exit.

DURABILITY The 16 mil thickness of the acrylic material used in the tape will provide years of reliable service.

EASY INSTALL The tape's peel and stick adhesive backing and ease of cutting makes installation simple and





DETAILS

MATERIAL 16 mil Acrylic

COLOR Photoluminescent, or Photoluminescent and Black

WIDTH 1 inch

LENGTH

• DT1: 20 linear feet

• DTO1: 150 linear feet

MOUNTING Surface

COMPLIANCE UL 1994, ASTM E2073, 2015 IBC/IFC 1025

TAPE







Obstacle Tape

MODELS

MODEL	WIDTH	LENGTH	DESCRIPTION
EM-DT1-20	1"	20 l.f.	Demarcation Tape, Acrylic, Self-Adhesive
EM-DT1-150	1"	150 l.f.	Demarcation Tape, Acrylic, Self-Adhesive
EM-DTO1-150	1"	150 l.f.	Obstacle Tape, Self-Adhesive

Note: Demarcation Tape is not recommended for floor applications. To illuminate floors, please see Safe-T-Lume Flat Demarcation Strips.

