



MODEL C1.875E-ECO

(SINGLE STAGE ECO-TREAD RIBS)

SPECIFICATIONS:

В

- $\langle 1 \rangle$ base: extruded aluminum alloy 6063 T-5
- 2 ECOTREAD: RECYCLED RUBBER SHEET

 8MM RECYCLED RUBBER GRANULES
 ENCAPSULATED IN A WEAR AND WATER
 RESISTANT ELASTOMERIC NETWORK. 2 PART
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. COLOR: BLACK (STANDARD), SAFETY YELLOW, BLACK-BLUE, BLACK-GRAY
- 7. LENGTH: 12'0" MAXIMUM
- 8. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

PROJECT: ARCHITECT: CONTRACTOR: QTY: PART#: STSB-C1.875E-ECO TITLE: V331, Stair Tread, Recycled Rubber - EcoTread, Short Nose, Alum Extruded Anchor, 9300 73rd Avenue North Minneapolis, MN 55428 NAME DATE SIZE DWG. NO. REV Nystrom STN STSB-C1.875E-ECO ShpDr Α 3/31/23 Α DRAWN RELEASED GLN WEIGHT: .69 LB SHEET 1 OF 1 3/31/23

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

1