

MODEL L1.875D-ECO

(SINGLE STAGE ECO-TREAD RIBS)

SPECIFICATIONS:

В

- $\langle 1 \rangle$ **BASE**: EXTRUDED ALUMINUM ALLOY 6063 T-5
- (2) ECOTREAD: RECYCLED RUBBER SHEET

 8MM RECYCLED RUBBER GRANULES
 ENCAPSULATED IN A WEAR AND WATER
 RESISTANT ELASTOMERIC NETWORK. 2 PART
- 3. BASE FINISH: MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- COLOR: BLACK (STANDARD), SAFETY YELLOW, BLACK-BLUE, BLACK-GRAY

- 7. LENGTH: 12'0" MAXIMUM
- 3. COUNTER SUNK HOLES PRE-DRILLED FOR A #10 FASTENER SPACED 3" FROM ENDS AND APPROXIMATELY 12" TO 15" O.C.
- 9. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

PROJECT: ARCHITECT: CONTRACTOR QTY: PART#: STSB-L1.875D-ECO TITLE: V430, Stair Tread, Recycled Rubber, Eco-Tread Long Nose, Drilled For Bolt In 9300 73rd Avenue North Minneapolis, MN 55428 NAME DATE SIZE DWG. NO. REV Nystrom STN STSB-L1.875D-ECO ShpDr Α Α DRAWN 3/31/23 RELEASED GLN WEIGHT: .90 LB SHEET 1 OF 1 3/31/23

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.