$\frac{1}{16}$ " MIN 1/**"** 83° 11/8"

MODEL A3D

(SINGLE STAGE RIBBED ABRASIVE BARS)

SPECIFICATIONS:

В

- (1) **BASE**: EXTRUDED ALUMINUM ALLOY 6063 T-5
- $\langle 2 \rangle$ **ABRASIVE**: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF **STEPS**
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. COLOR: BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT

- 7. **LENGTH**: 12'0" MAXIMUM
- 8. COUNTER SUNK HOLES PRE-DRILLED FOR A #10 FASTENER SPACED 3" FROM ENDS AND APPROXIMATELY 12" TO 15" O.C.
- 9. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

PROJECT: ARCHITECT: CONTRACTOR: QTY: PART#: STSB-A3D TITLE: V850, Stair Tread, Bar Ribbed Abrasive, Long Nose Angled, Drilled For Bolt In, 9300 73rd Avenue North Minneapolis, MN 55428 NAME DATE SIZE DWG. NO. REV Nystrom STN STSB-A3D ShpDr Α 3/11/11 Α DRAWN **BMH** RELEASED WEIGHT: 1.33 LB SHEET 1 OF 1 PE 3/11/11

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.