Valve

DETENTION CABINETS



DOOR 12 gauge Cold Rolled Steel

MOUNTING Recessed or Surface

OPTIONS Lock Prep, Lettering, Fire-Rated (2-hour), Polyester Finish

VALVE CABINET

МС	DEL	WALL	CAPACITY	ĸ	BOX I.D.	М		E O.D.			NING	ا ADA	(b) FRC
	1810	Recessed	2-1/2" Angle	18	18	8	21-3/4	21-3/4	19	19	8-1/2	Yes	Yes
	1815	Surface	Valve	18	18	8	-	-	-	-	-	No	No

VALVE AND EXTINGUISHER CABINET

	MODEL	WALL	CAPACITY	E	BOX I.D.		FRAME	E O.D.	WAL	L OPE	NING	SHELF	Ł	
	MODEL	MOUNTING						0					ADA	FRC
	DC-1870	Recessed	2-1/2" Angle Valve	14	40	8	17-3/4	43-3/4			8-1/2	12	Yes	Yes
-	DC-1875	Surface	2-1/2 gal. Water Ext.	14	40	8	-	-				12	No	No

Fire Blanket

CABINETS



Nystrom offers fire blanket cabinets in different styles to meet varying installation requirements. All styles of cabinets are equipped with a chemically treated fire blanket treated with fire resistant chemicals.

DOOR/BOX 20 gauge Cold Rolled Steel

FRAME 18 gauge Cold Rolled Steel

MOUNTING Recessed, Surface, Semi-recessed or trimless

OPTIONS Locks, Lettering, Fire-Rated (2-hour), Polyester Finish

FIRE BLANKET CABINET (INCLUDES BLANKET)

MODEL	WALL MOUNTING		BOX I.D.		اج ADA	∳ FRC
BC-6601	Surface	15	10	5	No	No

REPLACEMENT BLANKET

MODEL	SIZE
BC-6602	62 x 80

WRAP-AROUND BLANKET CABINET (INCLUDES BLANKET)

MODEL	WALL MOUNTING	BOX I.D.	اج ADA	(M) FRC
BC-6603	Surface	70-1/2 5-3/4 4-1/2	2 No	No

FIRE BLANKET AND EXTINGUISHER CABINET (INCLUDES BLANKET)

MODEL	WALL	NALL BOX I.D. COMPARTMENT UNTING BOX I.D. SIZE			COMPARTMENT		WALL OPENING			FOR USE WITH			
MODEL	MOUNTING						FIRE EXT'G	ADA	FRC				
BC-6605	Recessed - 5/8	14	40	8	14	28	8	15	41	8	EX-3002, EX-3020	Yes	Yes
BC-6606	Trimless	14	40	8	14	28	8	15	41	9	EX-3002, EX-3252	Yes	Yes
BC-6607	Semi-Recessed	14	40	8	14	28	8	15	41	6	EX-3202, EX-3320	Yes	Yes
BC-6609	Surface	16	42	9-1/2	16	30	9-1/2		-		EX-3002, EX-3410	No	No

Rain Hoods



BC-6605

Rain hoods help shield surface mounted cabinets from weather.

MATERIAL Cold Rolled Steel FINISH Polyester Coated

MODEL	CABINET WIDTH
OP-1927-04	11-1/4"
OP-1928-06	14-1/2"
OP-1927-70	16"
OP-1928-18	20"