

Coated Non-Precompressed Closed Cell Foam System

RECESSED APPLICATION (ESV)



BENEFITS

SIMPLICITY Minimal components and flexibility of seal allows for quick joint repairs.

HYDROSTATIC APPLICATION Standard system can accommodate up to 10 feet of hydrostatic pressure for below grade application.

DETAILS

MATERIAL Low Density, Closed Cell Foam with Silicone

SIZE 1/2 inch to 10 inches

- Sizes available in 1/4-inch increments starting at 1/2 inch
- Product supplied uncompressed at a standard 25% larger than the mean joint size

LENGTH 6 linear feet

APPLICATION Interior or Exterior

INSTALLATION Ceiling, Wall or Floors (non-traffic)

OPTIONS Terminations, Transitions, Seal Depths, Additional sizes upon request

MOVEMENT +/- 25% (Total 50%)

OPTIONS

TRANSITION



ORDER GUIDE

MODEL	APPLICATION	JOINT SIZE AT MEAN T°F	SEAL DEPTH
EJN-ESV-050	Surface	1/2" (13mm)	1-1/2" (38mm)
EJN-ESV-063	Surface	5/8" (16mm)	1-1/2" (38mm)
EJN-ESV-075	Surface	3/4" (19mm)	1-1/2" (38mm)
EJN-ESV-100	Surface	1" (25mm)	1-1/2" (38mm)
EJN-ESV-200	Surface	2" (51mm)	2" (51mm)
EJN-ESV-300	Surface	3" (76mm)	2" (51mm)
EJN-ESV-400	Surface	4" (102mm)	3" (76mm)
EJN-ESV-500	Surface	5" (127mm)	3" (76mm)
EJN-ESV-600	Surface	6" (152mm)	4" (102mm)
EJN-ESV-700	Surface	7" (178mm)	4" (102mm)
EJN-ESV-800	Surface	8" (203mm)	4" (102mm)
EJN-ESV-900	Surface	9" (229mm)	4" (102mm)
EJN-ESV-1000	Surface	10" (254mm)	4" (102mm)

Additional options available, email info@nystrom.com for more information.

SEAL COLORS

