

SEAL COLOR SELECTOR			
BLACK	_____	WHITE	_____
BEIGE	_____	GRAY	_____

2" SANTOPRENE SEAL
(B0020SN - SELECT COLOR)

1 1/2" [38mm]

1'-11 1/2" [597mm]

1'-7 1/2" [495mm]

GROUT
(BY OTHERS)

FINISH FLOORING
AS REQ'D

ALUMINUM PAN
ASSY (32082)

GROUT
(BY OTHERS)

1" [25mm]

2 1/4" [57mm]
ASSY HEIGHT

Ø 1/4" X 2-1/4" FH
TAPCON (32089) @ 12" O.C.

Ø 1/4" X 2-1/4" HH
TAPCON (32088) @ 18" O.C.

2" [51mm]

1'-2" [356mm]

ALUMINUM BASE
(32051)


ALUMINUM BASE
(32047)

11" [279mm]

Ø 1/4" X 2-1/4" FH
TAPCON (32089) @ 18" O.C.

FLOOR TO WALL BLOCKOUT APPLICATION

EXPOSED FINISH: MILL
MOVEMENT: +/- 50% NOMINAL JOINT WIDTH
SEAL THERMAL MOVEMENT: +/- 0.50"
STOCK LENGTHS: 10'-0"

PROJECT:			
ARCHITECT:			
CONTRACTOR:			
QTY:			
PART#:		EJN-FLP-1400W	
		TITLE: SEISMIC PAN FLOORING SYSTEM BLOCKOUT APPLICATION	
<small>9300 73rd Ave N., Minneapolis, MN 55428 800-547-2635 info@nystrom.com</small>			
NAME	DATE	SIZE	DWG. NO.
JMS	7/25/23	A	EJN-FLP-1400W
RELEASED		WEIGHT:	SHEET 1 OF 1