Seismic Aluminum Wall & Ceiling System

INTERIOR APPLICATION (RJI/RJIW)

BENEFITS

SEISMIC MOVEMENT System realigns itself with the self-centering bar, maintaining a safe, clean look.

COST SAVINGS The mill-finished cover plate offers a

budget-friendly alternative for walls and ceilings.



DETAILS

MATERIAL

6063-T5 Aluminum, Meets ASTM B221 6061-T6 Aluminum, Meets ASTM B209 5052 H32 Aluminum, Meets ASTM B209

FINISH Mill

MOVEMENT

Thermal: Horizontal and Vertical Seismic: Lateral Shear

MOUNTING Surface

JOINT SIZE 2 inches to 24 inches, see website for sizes larger than 12 inches

LENGTH 10 Linear Feet

APPLICATION Interior

INSTALLATION Wall or Ceiling

OPTIONS Fire barrier, Additional Materials, Sizes and

Finishes available upon request

INSTALLATION

WALL/CEILING TO WALL/CEILING **WALL/CEILING TO CORNER** For more information, download our Installation and Operating

Manuals (IOM) and Shop Drawings on nystrom.com

MODEL	APPLICATION	JOINT SIZE AT MEAN T°F	EXPOSED SIGHT LINE	TOTAL MOVEMENT
EJN-RJI-200	Wall/Ceiling to Wall/Ceiling	2" (51mm)	7" (178mm)	2" (51mm)
EJN-RJI-400	Wall/Ceiling to Wall/Ceiling	4" (102mm)	10" (255mm)	4" (102mm)
EJN-RJI-600	Wall/Ceiling to Wall/Ceiling	6" (152mm)	12" (305mm)	6" (152mm)
EJN-RJI-800	Wall/Ceiling to Wall/Ceiling	8" (203mm)	14" (356mm)	8" (203mm)
EJN-RJI-1000	Wall/Ceiling to Wall/Ceiling	10" (254mm)	17" (432mm)	10" (254mm)
EJN-RJI-1200	Wall/Ceiling to Wall/Ceiling	12" (305mm)	20" (508mm)	12" (305mm)
EJN-RJI-200W	Wall/Ceiling to Corner	2" (51mm)	4.5" (114mm)	1" (25mm)
EJN-RJI-400W	Wall/Ceiling to Corner	4" (102mm)	7" (178mm)	2" (51mm)
EJN-RJI-600W	Wall/Ceiling to Corner	6" (152mm)	9" (228mm)	3" (76mm)
EJN-RJI-800W	Wall/Ceiling to Corner	8" (203mm)	11" (280mm)	4" (102mm)
EJN-RJI-1000W	Wall/Ceiling to Corner	10" (254mm)	13.5" (343mm)	5" (127mm)
EJN-RJI-1200W	Wall/Ceiling to Corner	12" (305mm)	16" (406mm)	6" (152mm)

ORDER GUIDE

Sizes up to 24 inches available. See the full order guide at nystrom.com, or email info@nystrom.com for more information.