


FLOOR TO WALL NO BUMP APPLICATION

EXPOSED FINISH: MILL
 INFILL DEPTH = 1/8"
 MOVEMENT: +/- 25% JOINT WIDTH
 STOCK LENGTHS: 10'-0"

| | | | |
|--|----------|--|--------------------------|
| PROJECT: | | | |
| ARCHITECT: | | | |
| CONTRACTOR: | | | |
| QTY: | | | |
| PART#: | | EJN-SFP-1200W-125 | |
|  9300 73 rd Ave N., Minneapolis, MN 55428 800-547-2635 info@nystrom.com | | TITLE: SEISMIC ALUMINUM INFILL FLOORING SYSTEM - NO BUMP APPLICATION | |
| NAME | DATE | SIZE | DWG. NO. |
| DRAWN JPK | 09/24/24 | A | EJN-SFP-1200W-125 |
| RELEASED | | WEIGHT: | SHEET 1 OF 1 |

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING, IS SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE, WITHOUT THE WRITTEN PERMISSION OF NYSTROM, IS PROHIBITED. © 2020 NYSTROM, INC.