

ALUMINUM
FRAME (#D131)

FINISH FLOOR
(BY OTHERS)

8 7/8" [225mm]

6 1/2" [165mm]

3/16" ALUMINUM COVER PLATE
(#SF-CP-188-6.5-T2)

1"
[25mm]
ASSY.
HEIGHT

GROUT
(BY OTHERS)

Ø3/16" X 1 3/4" HH TAPCON
(#27529) @ 18" O.C.

(#DBAR10) w/ Ø1/4-20 X 1-1/2
FHMS/SS w/ NYLOK @ 18" O.C.

3 1/2" [89mm]


4" [102mm]

FLOOR TO FLOOR RECESSED BLOCKOUT APPLICATION

EXPOSED FINISH: MILL

MOVEMENT: +/- 50% NOMINAL JOINT WIDTH

STOCK LENGTHS: 10'-0"

PROJECT:			
ARCHITECT:			
CONTRACTOR:			
QTY:			
PART#:		EJN-SFG-400	
 9300 73rd Ave N., Minneapolis, MN 554428 800-547-2635 info@nystrom.com		TITLE: SEISMIC ALUMINUM FLOORING SYSTEM RECESSED BLOCKOUT APPLICATION	
NAME	DATE	SIZE	DWG. NO.
DRAWN JPK	12/27/22	A	EJN-SFG-400
RELEASED		WEIGHT:	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING, IS SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE, WITHOUT THE WRITTEN PERMISSION OF NYSTROM, IS PROHIBITED. © 2020 NYSTROM, INC.