

1-, 2- or 3-Hour Rated Seismic Pre-Compressed Horizontal Foam System RECESSED APPLICATION (FHES1/FHES2/FHES3)

BENEFITS

FIRE-RATED This 1-, 2- or 3-hour fire-rated horizontal expansion joint is watertight, and a primary seal for repair, retrofit and new installations.

MULTI-FUNCTIONAL This seal provides water and fire protection, color coordination, thermal insulation, sound attenuation and structural joint movement.

DETAILS

MATERIAL Foam with Silicone Bellow

SIZE

- 1/2 inch to 4 inches
- Additional Sizes Available in ¼-inch increments from 1 to 4 Inches
- 2 hour available up to 5 inch
- 2 hour available in 1/4 increments up to 5 inch

LENGTH 6.56 linear feet (2m)

APPLICATION Interior or Exterior

INSTALLATION Floor, Deck and Ceiling

CERTIFICATIONS UL 2079, ASTM E1966, E119, E1399, E90 and C518


OPTIONS Terminations, Transitions, Single Sided, Uncoated, and Pick Resistant Available

MOVEMENT

- Standard: +/- 50% (Total 100%)
- Also Available In: +/- 25% (Total 50%)



OPTIONS



For more information, download our Installation and Operating Manuals (IOM) and Shop Drawings on Nystrom.com



ORDER GUID

MODEL	JOINT SIZE AT MEAN T°F	TOTAL MOVEMENT	MODEL	JOINT SIZE AT MEAN T°F	TOTAL MOVEMENT	MODEL	JOINT SIZE AT MEAN T°F	TOTAL MOVEMENT
EJN-FHES1-050	1/2" (13mm)	4" (102mm)	EJN-FHES2-050	1/2" (13mm)	4" (102mm)	EJN-FHES3-050	1/2" (13mm)	4" (102mm)
EJN-FHES1-075	3/4" (19mm)	4" (102mm)	EJN-FHES2-075	3/4" (19mm)	4" (102mm)	EJN-FHES3-075	3/4" (19mm)	4" (102mm)
EJN-FHES1-100	1" (25mm)	4" (102mm)	EJN-FHES2-100	1" (25mm)	4" (102mm)	EJN-FHES3-100	1" (25mm)	4" (102mm)
EJN-FHES1-200	2" (51mm)	4" (102mm)	EJN-FHES2-200	2" (51mm)	4" (102mm)	EJN-FHES3-200	2" (51mm)	4" (102mm)
EJN-FHES1-300	3" (76mm)	4" (102mm)	EJN-FHES2-300	3" (76mm)	4" (102mm)	EJN-FHES3-300	3" (76mm)	4" (102mm)
EJN-FHES1-400	4" (102mm)	4" (102mm)	EJN-FHES2-400	4" (102mm)	4" (102mm)	EJN-FHES3-400	4" (102mm)	4" (102mm)
dditional options available, email EJN-FHES2-500				5" (127mm)	4" (102mm)	-		

info@nystrom.com for more information.