4" [102mm] -3/16" ALUMINUM COVER PLATE -(#SF-CP-188-3.5-B1-A90) 3 1/2" [89mm] 3/4" [19mm] 1" [25mm] ASSY. HEIGHT FINISH FLOOR -2" [51mm] (BY OTHERS) Ø3/16" FH DRYWALL OR MASONRY ANCHOR AS REQ'D. @ 18" O.C. (BY INSTALLER) **GROUT** (BY OTHERS) **ALUMINUM FRAME** (#D105) Ø3/16" x 1 3/4" HH TAPCON (#27529) @ 18" O.C. — 3 1/2" [89mm] —— 2" [51mm]

## FLOOR TO WALL NO BUMP BLOCKOUT APPLICATION

**EXPOSED FINISH: MILL** 

MOVEMENT: +/- 25% NOMINAL JOINT WIDTH

STOCK LENGTHS: 10'-0"

	PROJECT:						
	ARCHITECT:						
	CONTRACTOR:						
	QTY:						
	PART#:  Nation  9300 73'd Ave N., Minneapolis, MN 554428 800-547-2635 info@nystrom.com				EJN-SFP-200W		
					TITLE: SEISMIC ALUMINUM FLOORING SYSTEM NO BUMP BLOCKOUT APPLICATION		
		NAME	DATE	SIZE	DWG. NO. EJN-SFP-200\	N	REV <b>A</b>
	DRAWN JPK 12/27/22 A RELEASED WE				IGHT:	SHEET 1 OF 1	

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING, IS SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE, WITHOUT THE WRITTEN PERMISSION OF NYSTROM, IS PROHIBITED. © 2020 NYSTROM, INC.

2