

Elastomeric


TWIN SEAL SYSTEM (TMM/TMMw)

BENEFITS

COORDINATING CORNERS Available with corner option for a complete floor and wall solution.

COORDINATION Designed for both horizontal and vertical applications, this system provides a continuous coordinated look and feel.

COMPLEMENTARY SEAL COLORS Available in four elastomeric seal color options: beige, white, gray or black.



DETAILS

MATERIAL 6063-T6 Aluminum

FINISH Mill and Rubber Seals

MOVEMENT

Thermal: Horizontal and Vertical

MOUNTING Surface

JOINT SIZE 2 inches to 6 inches

LENGTH 10 Linear Feet

LOAD Pedestrian and Light Cart

INSTALLATION Floor or Wall

OPTIONS Seal Color, Moisture Barrier, Fire Barrier

FLOOR-TO-WALL/CORNER For more information, download our Installation and Operating Manuals (IOM) and Shop Drawings on nystrom.com

INSTALLATION

SEAL COLORS Beige White Gray Black

ORDER GUIDE				
MODEL	INSTALLATION	JOINT SIZE AT MEAN T°F	SYSTEM WIDTH	TOTAL MOVEMENT
EJN-TMM-200	Floor to Floor	2" (51mm)	7.75" (197mm)	4.25" (108mm)
EJN-TMM-400	Floor to Floor	4" (102mm)	9.75" (248mm)	6.25" (159mm)
EJN-TMM-600	Floor to Floor	6" (152mm)	11.75" (298mm)	8.25" (210mm)
EJN-TMM-200W	Floor to Wall	2" (51mm)	4.88" (124mm)	2.5" (64mm)
EJN-TMM-400W	Floor to Wall	4" (102mm)	6.88" (175mm)	4.5" (114mm)
EJN-TMM-600W	Floor to Wall	6" (152mm)	8.88" (226mm)	6.5" (165mm)