

NEW



Perimeter Air Return

HVAC ACCESS DOOR

The Perimeter Air Return (PAR) Access Door delivers a clean, elegant, louver-free solution while providing make up air to appliances that are discreetly concealed behind the door. The PAR door provides easy access for service and repair of equipment.

FEATURES

INSULATED 1½-inch thick Linacoustic® duct liner provides superior acoustical and thermal performance.

RETURN AIR 1 inch gap around the perimeter of the door for air return.

REMOVEABLE DOOR

CUSTOM SIZES Custom sizes are available, from 20 inches by 36 inches to 36 inches by 72 inches.

PREHUNG DOOR ALTERNATIVE Requires no additional hardware or trim. Reduce install time. Provides a sleek integrated finished look.

DETAILS

DOOR

- Removeable
- 20 gauge Steel

FRAME 16 gauge Steel

SIZE

- Min: 20 inches by 36 inches
- Max: 36 inches by 72 inches

INSTALLATION Wall

FLANGE 1¼ inch Exposed, Drywall Bead

HINGE Concealed Hinge

AIR RETURN 1 inch gap around door

FINISH White Powder Primer Coat

INSULATION 1½ inch Linacoustic Duct Liner

LATCH Magnetic

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH
PAR				X	
	T 1¼ inch Flange W Drywall Bead	J Magnetic Latch C Screwdriver Cam Latch L Keyed Cam Lock H Hex Head Cam Latch P Pinned Hex Cam Latch	Standard Sizes		
			24" x 36"	30" x 54"	34" x 48"
			24" x 48"	30" x 60"	34" x 60"
			28" x 48"	30" x 72"	34" x 72"
			28" x 54"	32" x 48"	36" x 60"
			28" x 60"	32" x 60"	36" x 66"
			30" x 48"	32" x 72"	36" x 72"

Rough opening is door size + ¼ inch.

Additional sizes available, call for more information.

Linacoustic is a registered trademark of Johns Manville © 2024

MATERIALS



White Powder
Primer Coat

FLANGES



1¼-inch Flange



Drywall Bead

LATCHES




Magnetic
Latch



Screwdriver
Cam Latch



Key Operated
Cam Lock



Hex Head
Cam Latch



Pinned Hex
Cam Latch