

SEAL COLOR SELECTOR
 BLACK _____ WHITE _____
 BEIGE _____ GRAY _____


USE CONTINUOUS
 STRUCTURAL ADHESIVE
 TO ATTACH FRAME TO THIS
 SIDE (BY INSTALLER)

2"
 [51mm]

Ø3/16" FH DRYWALL OR MASONRY
 ANCHOR AS REQ'D. @ 18" O.C.
 (BY INSTALLER) TYP.

SANTOPRENE SEAL (#C143SN)
 SPECIFY COLOR

ALUMINUM FRAME (#32000)




WALL & CEILING RECESSED APPLICATION

EXPOSED FINISH: MILL

MOVEMENT: +/- 25% NOMINAL JOINT WIDTH

STOCK LENGTHS: 10'-0"

PROJECT:			
ARCHITECT:			
CONTRACTOR:			
QTY:			
PART#:		EJN-LCWF-200W	
 9300 73 rd Ave N., Minneapolis, MN 554428 800-547-2635 info@nystrom.com		TITLE: ELASTOMERIC CORRIDOR WALL & CEILING SYSTEM RECESSED APPLICATION	
NAME	DATE	SIZE	DWG. NO.
DRAWN	JPK	09/11/23	EJN-LCWF-200W
RELEASED			WEIGHT:
			SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING, IS SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE, WITHOUT THE WRITTEN PERMISSION OF NYSTROM, IS PROHIBITED. © 2020 NYSTROM, INC.