

IF REQUIRED, SEALANT  
OR GROUT (BY OTHERS)

ADJUST TO ACCEPT  
FINISH FLOORING  
(BY OTHERS)

ALUMINUM GLIDE  
(#29486)

ALUMINUM COVER  
(#29498)

ALUMINUM FRAME  
(#29478)

Ø1/4" x 1-3/4" THREADED  
ANCHOR (#31860) @ 24" O.C.

5 1/2" [140mm]

2 1/4" [57mm]

1"  
[25mm]


1" [25mm] 2 5/16" [59mm]

### ***ALUMINUM GLIDE FLOORING SYSTEM NO-BUMP BLOCKOUT APPLICATION***

EXPOSED FINISH: MILL

MOVEMENT: +/- 50% JOINT WIDTH

STOCK LENGTHS: 10'-0"

PROJECT:			
ARCHITECT:			
CONTRACTOR:			
QTY:			
PART#:		EJN-NBF-100	
 9300 73 <sup>rd</sup> Ave N., Minneapolis, MN 554428 800-547-2635 info@nystrom.com		TITLE: SEISMIC ALUMINUM GLIDE FLOORING SYSTEM NO-BUMP BLOCKOUT APPLICATION	
	NAME	DATE	SIZE
DRAWN	JPK	05/31/23	A
RELEASED			
DWG. NO.		EJN-NBF-100	
WEIGHT:		SHEET 1 OF 1	