

IF REQUIRED, SEALANT OR GROUT (BY OTHERS)

ADJUST TO ACCEPT FINISH FLOORING (BY OTHERS)

8 1/2" [216mm]

3 1/4" [83mm]

ALUMINUM COVER (#29499)

1" [25mm]

ALUMINUM FRAME (#29480)

Ø1/4" x 1-3/4" THREADED ANCHOR (#31860) @ 24" O.C.

ALUMINUM GLIDE (#29488)


2" [51mm]

ALUMINUM GLIDE FLOORING SYSTEM NO-BUMP BLOCKOUT APPLICATION

EXPOSED FINISH: MILL

MOVEMENT: +/- 50% JOINT WIDTH

STOCK LENGTHS: 10'-0"

PROJECT:				
ARCHITECT:				
CONTRACTOR:				
QTY:				
PART#:		EJN-NBF-200		
 9300 73 rd Ave N., Minneapolis, MN 554428 800-547-2635 info@nystrom.com		TITLE: SEISMIC ALUMINUM GLIDE FLOORING SYSTEM NO-BUMP BLOCKOUT APPLICATION		
NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	JPK	05/30/23	A	EJN-NBF-200
RELEASED			WEIGHT:	SHEET 1 OF 1