

IF REQUIRED, SEALANT  
OR GROUT (BY OTHERS)

ADJUST TO ACCEPT  
FINISH FLOORING  
(BY OTHERS)

10 1/2" [267mm]

4" JT. FLOOR/FLOOR  
ALUMINUM GLIDE  
(#32007)

3 1/4" [83mm]

ALUMINUM COVER  
(#29499)

1"  
[25mm]

ALUMINUM FRAME  
(#29480)

Ø1/4" x 1-3/4" THREADED  
ANCHOR (#31860) @ 24" O.C.

4" [102mm]


3 5/16" [84mm]

**ALUMINUM GLIDE FLOORING SYSTEM NO-BUMP BLOCKOUT APPLICATION**

EXPOSED FINISH: MILL

MOVEMENT: +/- 50% JOINT WIDTH

STOCK LENGTHS: 10'-0"

PROJECT:			
ARCHITECT:			
CONTRACTOR:			
QTY:			
PART#:		EJN-NBF-400	
 9300 73 <sup>rd</sup> Ave N., Minneapolis, MN 554428 800-547-2635 info@nystrom.com		TITLE: SEISMIC ALUMINUM GLIDE FLOORING SYSTEM NO-BUMP BLOCKOUT APPLICATION	
	NAME	DATE	SIZE
DRAWN	JPK	06/29/23	A
RELEASED			
DWG. NO.		EJN-NBF-400	
WEIGHT:		SHEET 1 OF 1	