

Ø3/16" DRYWALL OR MASONRY ANCHOR AS REQ'D. @ 18" O.C. (BY INSTALLER)

1 3/4" [45mm]

1" [25mm]

ALUMINUM FRAME (#29466)

5/8" [16mm]

OPTIONAL RECESSED MOUNTING

IF REQUIRED, SEALANT OR GROUT (BY OTHERS)

ALUMINUM COVER (#29465)

SLIDE GASKET (#1309)

ALUMINUM GLIDE (#29473)


4 1/2" [114mm]

ALUMINUM GLIDE WALL & CEILING SYSTEM SURFACE APPLICATION

EXPOSED FINISH: CLEAR ANODIZED

MOVEMENT: +/- 50% NOMINAL JOINT WIDTH

STOCK LENGTHS: 10'-0"

PROJECT:				
ARCHITECT:				
CONTRACTOR:				
QTY:				
PART#:		EJN-NBW-100		
 9300 73rd Ave N., Minneapolis, MN 554428 800-547-2635 info@nystrom.com		TITLE: SEISMIC ALUMINUM GLIDE WALL & CEILING SYSTEM SURFACE APPLICATION		
NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	JPK	05/31/23	A	EJN-NBW-100
RELEASED			WEIGHT:	SHEET 1 OF 1