Ø3/16" FH DRYWALL OR MASONRY -– 7" [177mm] — ANCHOR AS REQ'D. @ 18" O.C. (BY INSTALLER) **ALUMINUM WALL FRAME** (#2686)- 1/4" [7mm] - ALUMINUM HINGE COVER PLATE (#2628) 2 5/8" [65mm] 7/8" [22mm] · 3" [76mm] -

| Dimension Chart | | | | | | |
|--------------------|-----------------|-------------------------------|----------------|----------------|-------------------------|-----------|
| Nystrom Model # | System Width | Joint Opening @ Installation | , | | Vertical Movement (Max) | |
| | | | (Pedestrian)* | (Vehicle) ** | Up | Down |
| EJN-PD-300W | 7" (117mm) | 3" (76mm) | 6 3/8" (162mm) | 5 3/8" (137mm) | 1/4" (6mm) | 2" (51mm) |

^{*} Pedestrian Loads (only) during normal design conditions.

FLOOR-TO-WALL HEAVY DUTY SYSTEM

EXPOSED FINISH: MILL STOCK LENGTHS: 10'-0"

PROJECT: ARCHITECT: CONTRACTOR: QTY: EJN-PD-300W PART#: TITLE: nystrom ALUMINUM HINGED **HEAVY DUTY SYSTEM** 9300 73rd Ave N., Minneapolis, MN 554428 800-547-2635 SURFACE APPLICATION info@nystrom.com NAME DATE SIZE DWG NO REV EJN-PD-300W **DRAWN** JPK 2/17/2023 RELEASED WEIGHT: SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING, IS SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE, WITHOUT THE WRITTEN PERMISSION OF NYSTROM, IS PROHIBITED. © 2020 NYSTROM, INC.

^{**} Vehicle Loads (only) during normal design (low acceleration) design conditions.