3/8" ALUMINUM -- 11 3/4" [298mm] --**COVER PLATE** (#PT-CP-2/4) - 9" [229mm] -3/16" ALUMINUM JOINTCRETE™ HEADER MATERIAL Ø1/4-20 x 5/8" FHMS/SST @ 18" O.C. **WING PLATE** (*NOT INCLUDED W/ SYSTEM) (#31803)(#PTX-WP-2) 1 1/2" [39mm] ASSY HEIGHT - ALUMINUM FRAME-MODIFIED JOINTCRETE™ PRIMER (#W001-M) 10 MIL MIN. THICKNESS A ~ A . 4 (*NOT INCLUDED W/ SYSTEM) -Ø3/8" x 3" TAPCON SCREW ANCHOR (#32003) @ 18" O.C. - 4 4 4 **CENTERING BAR MECHANISM** (#WBAR12-KIT) @ 18" O.C. **MOISTURE BARRIER (#21951)** - 6 1/2" [165mm] ———— 2" [51mm] -

FLOOR-TO-FLOOR RECESSED BLOCKOUT APPLICATION

EXPOSED FINISH: MILL

MOVEMENT: + / - 50% NOMINAL JOINT WIDTH

STOCK LENGTHS: 10'-0"

	PROJECT:								
	ARCHITECT: CONTRACTOR: QTY: PART#: Anystrom 9300 73rd Ave N., Minneapolis, MN 554428 800-547-2635								
					EJN-PTX-200				
					TITLE: SEISMIC ALUMINUM HEAVY DUTY FLOORING SYSTEM				
	Îr	info@nystrom.com				RECESSED BLOCKOUT APPLICATION			
		NAME	DATE	SIZE	DWG NO	E IN DTY	(200	REV	
:	DRAWN	JPK	06/16/23	A		EJN-PTX-200		Α	

SHEET 1 OF 1

WEIGHT:

RELEASED

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING, IS SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE, WITHOUT THE WRITTEN PERMISSION OF NYSTROM, IS PROHIBITED. © 2020 NYSTROM, INC.

2