

MOISTURE BARRIER (#21954) SET IN BED OF CONTINUOUS SEALANT (BY OTHERS) TYPICAL BOTH SURFACES

Ø3/16" x 1 3/4" PFH SILVER TAPCON (#1565) @ 18" O.C.

#DBAR26L w/ Ø1/4-20 x 1-1/2" PPMS/SS (#31907) @ 18" O.C.

ALUMINUM FRAME (#D212)

1" [25mm]

SPACER (#1216)

.090" ALUMINUM COVER PLATE (#RJ-CP-16W)

1/2" [13mm]

VINYL (#SE23)

2" [51mm]

2" [51mm]

Ø3/16" x 1 3/4" PFH SILVER TAPCON (#1565) @ 12" O.C.

1'-9" [533mm]


1'-4" [406mm]

ALUMINUM WALL SYSTEM EXTERIOR APPLICATION

EXPOSED FINISH: MILL

MOVEMENT: +/- 25% NOMINAL JOINT WIDTH

STOCK LENGTHS: 10'-0"

PROJECT:			
ARCHITECT:			
CONTRACTOR:			
QTY:			
PART#:		EJN-RJE-1600W	
 9300 73 rd Ave N., Minneapolis, MN 55428 800-547-2635 info@nystrom.com		TITLE:	
		SEISMIC ALUMINUM WALL SYSTEM EXTERIOR APPLICATION	
	NAME	DATE	SIZE
DRAWN	JPK	03/19/24	A
RELEASED			
DWG. NO.		EJN-RJE-1600W	
WEIGHT:		SHEET 1 OF 1	