- 2" [51mm] → MOISTURE BARRIER (#21951) SET IN BED -OF CONTINUOUS SEALANT (BY OTHERS) #DBAR5 w/ Ø1/4-20 x 1-1/2" LG. PPMS/SS **TYPICAL BOTH SURFACES** (#31907) @ 18" O.C. (Ø3/16" x 1-3/4" LG. PFH SILVER TAPCON (#1565) @ 18" O.C. (TYP) 1" [25mm] 1/2" [13mm] **ALUMINUM FRAME SPACER (#1216)** (#D212) VINYL (#SE23) .090" ALUMINUM COVER PLATE — (#RJ-CP-2) _ 7" [178mm] ———

ALUMINUM WALL SYSTEM EXTERIOR APPLICATION

EXPOSED FINISH: MILL

MOVEMENT: +/- 50% NOMINAL JOINT WIDTH

STOCK LENGTHS: 10'-0"

	PROJECT:							
	ARCHITECT:							
	CONTRACTOR:							
	QTY:							
	PART#:				EJN-RJE-200			
					TITLE: SEISMIC ALUMINUM WALL SYSTEM EXTERIOR APPLICATION			
		NAME	DATE	SIZE	DWG. NO.		REV	
:	DRAWN	JPK	03/06/24	Α	EJN-RJE-20	U	Α	
	RELEASED WE			WE	GHT:	SHEET 1	OF 1	

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING, IS SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE, WITHOUT THE WRITTEN PERMISSION OF NYSTROM, IS PROHIBITED. © 2020 NYSTROM, INC.

2