

MOISTURE BARRIER (#21951) SET IN BED OF CONTINUOUS SEALANT (BY OTHERS) TYPICAL BOTH SURFACES

#10-24 x 1-1/2" LG. PPHMS/SS (#31905) @ 18" O.C.

CENTERING MECHANISM (#B2100) ASSEMBLY

Ø3/16" x 1-3/4" LG. PFH SILVER TAPCON (#1565) @ 18" O.C. (TYP)

3/8" [9mm]

ALUMINUM FRAME (#D203)

VINYL (#SE23)

0.090" ALUMINUM COVER PLATE (#FCT-CP-2CLR)

7" [177mm]


2" [51mm]

EXTERIOR WALL SYSTEM SURFACE MOUNT APPLICATION

EXPOSED FINISH: CLEAR ANODIZED

MOVEMENT: +/- 50% NOMINAL JOINT WIDTH

STOCK LENGTHS: 10'-0"

PROJECT:			
ARCHITECT:			
CONTRACTOR:			
QTY:			
PART#:		EJN-RJX-200	
 9300 73 rd Ave N., Minneapolis, MN 554428 800-547-2635 info@nystrom.com		TITLE: SEISMIC ALUMINUM EXTERIOR WALL SYSTEM SURFACE MOUNT APPLICATION	
NAME	DATE	SIZE	DWG. NO.
DRAWN JPK	07/24/23	A	EJN-RJX-200
RELEASED		WEIGHT:	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING, IS SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE, WITHOUT THE WRITTEN PERMISSION OF NYSTROM, IS PROHIBITED. © 2020 NYSTROM, INC.