

MOISTURE BARRIER (#21953) SET IN BED OF CONTINUOUS SEALANT (BY OTHERS) TYPICAL BOTH SURFACES

CENTERING MECHANISM (#DBAR20) ASSEMBLY

Ø1/4-20 x 1-1/2" LG. PPHMS (#31907) @ 18" O.C.

ALUMINUM FRAME (#D211)

Ø3/16" x 1-3/4" LG. PFH SILVER TAPCON (#1565) @ 18" O.C. (TYP)

VINYL (#SE23)

SPACER (#1216)

0.090" ALUMINUM COVER PLATE (#FCT-CP-8CLR)

3/8" [9mm]

1'-4 1/2" [419mm]

EXTERIOR WALL SYSTEM SURFACE MOUNT APPLICATION

EXPOSED FINISH: CLEAR ANODIZED
 MOVEMENT: +/- 50% NOMINAL JOINT WIDTH
 STOCK LENGTHS: 10'-0"

PROJECT:		
ARCHITECT:		
CONTRACTOR:		
QTY:		
PART#:		EJN-RJX-800
 9300 73rd Ave N., Minneapolis, MN 554428 800-547-2635 info@nystrom.com		TITLE: SEISMIC ALUMINUM EXTERIOR WALL SYSTEM SURFACE MOUNT APPLICATION
NAME	DATE	SIZE
DRAWN JPK	07/24/23	A
RELEASED		
DWG. NO.		EJN-RJX-800
WEIGHT:		
SHEET 1 OF 1		