SANTOPRENE SEAL -5" [126mm]-ALUMINUM COVER (#W30-34-91) (#D109) SEALANT -SS ANGLE: 1/8" x 1-1/4" x 1-1/4"-(BY OTHERS) (#32109)**TOPPING SLAB OR PAVERS-**(BY OTHERS) 3 5/16" [84mm] Ø1/4-20 x 3/4" LG. FHMS SST-@ 18" O.C. (#1306) SELF ADHERING SHEET-В MEMBRANE x 18" WIDE **ALUMINUM FRAME-**Ø1/4" x 1-3/4" FH SILVER TAPCON (#W006) (#32108)(#31860) @ 12" O.C. COAT ENTIRE SURFACE BEHIND FLAP 3 3/4" W/ SEALANT (BY INSTALLER) PRIOR TO [95mm] ATTACHING ALUMINUM COVER ASSY. **HEIGHT** Ø5/16-18 x 5/8" LG. FHMS SST @ 18" O.C. (#32132) WATERPROOFING (BY OTHERS) ∠ ALUMINUM BASE ANGLE 1/4" x 2-1/2" x 2-1/2" (#32110) ///// -MOISTURE BARRIER Ø5/16" x 2-1/4" LG. BUTTON TRUX HEAD TAPCON @ 18" O.C. (#32111) (#21952)4" [102mm] PROJECT: ARCHITECT: **TOPPING SLAB DECK APPLICATION** CONTRACTOR: EXPOSED SEAL FINISH: BLACK QTY: EXPOSED METAL FINISH: MILL PART#: EJN-TSS-400W-400 MOVEMENT RANGE: +2 1/4" [57mm] / -1 1/2" [38mm] TITLE: nvstrom[®] STOCK LENGTHS: 10'-0" SEISMIC EXTERIOR PLAZA SYSTEM TOPPING SLAB DECK APPLICATION Ave N., Minneapolis, MN 55428 800-547-2635 info@nystrom.com NAME DATE SIZE DWG NO. REV EJN-TSS-400W-400 Α PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING, IS SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR **DRAWN** JPK 11/08/23

RELEASED

WEIGHT:

SHEET 1 OF 1

2

AS A WHOLE, WITHOUT THE WRITTEN PERMISSION OF NYSTROM, IS PROHIBITED. © 2020 NYSTROM, INC.