







OPTIONS

RELEASED

Gasketing Installed

Perforated Door,

in² Free Area

SHEET 1 OF 2

Door Liner, 20 Ga Steel

Ceiling Mount

PROJECT: ARCHITECT: CONTRACTOR: QTY: PART#: PART#: TITLE: PROJECT: ARCHITECT: CONTRACTOR: QTY: PART#: DATE SIZE DRAWN PROJECT: ARCHITECT: DWG. NO. Nystrom AD HVACT ShpDr

WEIGHT:

SPECIFICATIONS:

1 DOOR: 20 Ga Steel

2 FRAME: 16 Ga Steel, 1.25" Flange

3 FINISH: White Powder Pimer Coat

4 HINGE: Concealed Pin Hinge

5 LATCH:

(6) INSULATION: 1.5" Fiberglass Insulation for

Sound Attenuation

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED. ©2021 NYSTROM, INC.

ROUGH OPENING:

CLEAR OPENING:

DEGREE OF OPENING: 120°

2

1

