

NEW



Clean Room

ACCESS DOOR

The Clean Room Access Door is ideal for applications where moisture or air movement is a consideration through walls or ceilings. Gasketing on all four sides ensures continuity of the seal and can be used on both interior and exterior applications.

FEATURES

CUSTOM SIZES Custom sizes are available, from 8 inches by 8 inches to 36 inches by 60 inches.

CERTIFICATION Tested in accordance with ASTM E283 and ASTM E331.

DETAILS

DOOR 16 gauge Galvanneal Steel

FRAME 16 gauge Galvanneal Steel

SIZE

- Min: 8 inches by 8 inches
- Max: 36 inches by 60 inches

INSTALLATION Wall or Ceiling

FLANGE 3/4 inch Exposed

HINGE Continuous Stainless Steel Piano Hinge

GASKET Black, closed cell blended rubber; EPDM/Neoprene/SBR

FINISH Off-White Prime Coat or #4 Satin (Stainless Steel)

CERTIFICATION ASTM E283 and ASTM E331

ORDER GUIDE

BASE	LATCH	WIDTH	X	LENGTH	OPTION
MNT			X		
	C Screwdriver Cam Latch	Standard Sizes			S Stainless Steel, Type 304
	H Hex Cam Latch			20" x 20"	
	L Key Operated			24" x 24"	
	Cam Lock			24" x 36"	
	MP Mortise Prep			30" x 30"	
	MPI Mortise Cam Lock Installed	18" x 18"		36" x 36"	
	TP Non-Locking 2 Position Handle				

Rough opening is door size.
Additional sizes available, call for more information.

MATERIALS



Off-White
Prime Coat



#4 Satin
(Stainless Steel)

FLANGES



3/4-inch Flange

LATCHES



Screwdriver
Cam Latch



Hex Cam Latch



Key Operated
Cam Lock



Mortise
Lock Prep