UPDATED



Gasketed

ACCESS DOOR

The Gasketed Access door is an all purpose access door that reduces sound transmission and minimizes air filtration.

FEATURES

CUSTOM SIZES Custom sizes are available, from 6 inches by 6 inches to 36 inches by 36 inches.

OPTIONAL STAINLESS STEEL The spot-free design on the face of the door gives an aesthetically pleasing appearance

DETAILS

DOOR 16 gauge Steel FRAME 16 gauge Steel

SIZE

• Min: 6 inches by 6 inches

• Max: 36 inches by 72 inches or 48 inches by 48 inches

INSTALLATION Ceiling or wall

FLANGE 11/4 inch Exposed, Drywall Bead

HINGE Concealed Pin

GASKET EPDM

FINISH White Powder Coat (Steel) or #4 Satin (Stainless Steel)



White Powder Coat

MATERIALS

#4 Satin Stainless Steel

FLANGES





1¼-inch Flange

LATCHES



Screwdriver

Cam Latch





Key Operated Cam Lock

Mortise Lock Prep



Pinned Hex Cam Latch

Hex Cam Latch

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	Χ	LENGTH	OPTIONS
G				Х		
	T 1¼ inch Flange W Drywall Bead	C Screwdriver Cam Latch L Key Cam Latch P Pinned Hex Cam Latch M Mortise Prep (1½ inch) Prep H Hex Head Cam	Standard 6" x 6" 8" x 8" 10" x 10" 12" x 12" 12" x 18" 12" x 24" 14" x 14" 16" x 16" 18" x 18" 18" x 24"	2 2 2 2 2 2 2 3 3 3	0" x 30" 2" x 22" 2" x 30" 4" x 24" 4" x 30" 4" x 36" 0" x 30" 0" x 36" 2" x 32" 6" x 36"	B Galvannealed S Stainless Steel, Type 304

Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.