

SPECIFICATIONS:

⟨**1**⟩COVER:

11 GA (.090) ALUM, STIFFENED TO WITHSTAND A LIVE LOAD OF 40PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN.

- ⟨**2**⟩ **LINER:** 18 GA (.040) ALUM
- (3) CURB: 11 GA (.090) ALUM, CURB COUNTERFLASH WITH EZ TABS.
- 4 FINISH: MILL
- (5) INSULATION: 1" POLYISO R-6 (5.6 LTTR) IN CURB,
 - 1" POLYSTYRENE R-4 (3.8 LTTR) IN COVER.
- **(6)** GASKET:

EXTRUDED EPDM RUBBER ADHESIVE BACKED GASKET SEAL CONTINUOUS AROUND COVER.

- $\langle \overline{7} \rangle$ SPRING: GAS SPRING WITH DAMPER FOR SMOOTH, CONTROLLED, COUNTERBALANCED LIFT ASSISTANCE.
- (8) HINGE: PINTLE HINGE WITH STAINLESS STEEL HINGE PINS.
- (9) HOLD OPEN ARM:

ZINC PLATED STEEL AUTOMATIC HOLD OPEN ARM LOCKS COVER IN FULLY OPEN POSITION WITH RED GRIP HANDLE PULL RELEASE.

(10) LATCH:

ZINC PLATED STEEL SLAM LATCH, HOLDS COVERS CLOSED AGAINST WIND UPLIFT, INTERIOR AND EXTERIOR HANDLES WITH PADLOCK

11) PULL HANDLE: INTERIOR PULL DOWN HANDLE

NOTES:

-WHEN INSTALLING ON A PITCHED ROOF UP TO 7:12. THE HINGE SIDE(LENGTH)MUST BE PARALLEL TO THE SLOPE.

- WIDTH X LENGTH DIMENSIONS ARE MEASURED INSIDE CURB TO INSIDE CURB. THE WIDTH IS HINGE TO LATCH AND LENGTH IS HINGED SIDE.

ROOF HATCH SIZE 36" (WIDTH) x 96" (LENGTH)

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED. @2020 NYSTROM, INC.

	PROJECT: ARCHITECT: CONTRACTOR: QTY: PART#:						
					A3696 TITLE: RHUA36X96S1T Roof Hatch, Personnel, 36x96, S Dr, Zinc Hdw, Alum, Mill, Sngl Wall Curb		
9300 73rd Avenue North Minneapolis, MN 55428				'n°			
		NAME	DATE	SIZE	DWG. NO.		REV
	DRAWN	DWO	1/3/22	Α	Nystrom RH A3696 ShpDr		A
	RELEASED	DWO	1/3/22	WE	GHT: 184 LBS	SHEET 1	OF 2

