



SPECIFICATIONS:

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-5
- ② **ECOTREAD:** RECYCLED RUBBER SHEET
8MM RECYCLED RUBBER GRANULES
ENCAPSULATED IN A WEAR AND WATER
RESISTANT ELASTOMERIC NETWORK. 2 PART
- 3. **BASE FINISH:** MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL
TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING
SHALL BE FULL LENGTH OF STEPS, LESS 1/8"
CLEARANCE
- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW,
BLACK-BLUE, BLACK-GRAY

- 7. **LENGTH:** 12'0" MAXIMUM
- 8. **COUNTER SUNK HOLES PRE-DRILLED FOR A #10
FASTENER SPACED 3" FROM ENDS AND
APPROXIMATELY 12" TO 15" O.C.**
- 9. **UL 1994 LISTED: COMBINED WIDTH OF PHOTO-
LUMINESCENT MATERIAL SHALL NOT BE LESS
THAN 1"**

LENGTH	QTY	COLOR

PROJECT:				
ARCHITECT:				
CONTRACTOR:				
QTY:				
PART#:		STRB-A9D-ECO		
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE:		
		V500S, Stair Tread, Recycled Rubber, 14 Eco-Tread Ribs Long Nose Angled, Drilled For Bolt In,		
NAME	DATE	SIZE	DWG. NO.	REV
DRAWN: DKL	3/31/23	A	Nystrom STN STRB-A9D-ECO ShpDr	A
RELEASED: GLN	3/31/23	WEIGHT: 3.75 LB		SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.