



February 2025

RE: Sustainability Statement

Nystrom certifies and provides the following information for use in achieving LEED v4.1 credit for the specification of our Thermally Broken Retrofit Roof Hatch.

**Products:** Thermally Broken Retrofit Roof Hatch  
**Model:** RHRT

Manufacturing Information:

- Final Assembly Location: Minneapolis, MN
- Extraction point is not within 500 miles of manufacturing

#### **LEED Credit Contributions**

**Category: Materials and Resources (MR)**

**Credit: Sourcing of Raw Materials (1-2 Points)**

*Recycled Content:* Nystrom Thermally Broken Retrofit Roof Hatch is constructed of:

- 69-72% Aluminum Alloy, which suppliers estimate consists of 80% Recycled Content (40-80% Pre-Consumer Content; 10-30% Post-Consumer Content)
- 12.5-15% Steel Alloy, for which LEED® allows a default value of 25% post-consumer recycled content

**Category: Materials and Resources (MR)**

**Credit: Material Ingredients**

*Material Ingredient Reporting (1 Point):* A published, complete Health Product Declaration (HPD) is available for our [Thermally Broken Retrofit Roof Hatch](#), with full disclosure of known hazards of all substances present at or above 0.1% (1000 ppm), in compliance with the Health Product Declaration Open Standard. Nystrom Thermally Broken Retrofit Roof Hatch can therefore contribute one whole product to the 20 different permanently installed products required for this credit.

**Category: Indoor Environmental Quality (EQ)**

**Credit: Low-Emitting Materials (Up to 3 Points)**

Nystrom Thermally Broken Retrofit Roof Hatch is constructed of at least 88% powder-coated, plated or anodized metals, which LEED considers inherently non-emitting sources of VOCs.

If you require any further information, please contact us at (800) 547-2635.