

Acoustic

FOAM SEALANT (QTT/QTG)

Acoustic foam gap filler. Nystrom's Acoustic Foam Sealant is a filler used to control sound, draft, heat, cold and block dust for interior, non-moving joints and gaps and should be used when the joint is visible in walls or interior glass windows. It is colored, versatile and ideally suited to filling gaps between the ends of permanent, semi-permanent, or movable partitions, head of wall and other conditions.

FEATURES

AESTHETIC GAP FILLER The acoustic glazing sealant (QTG) is coated and finished on three sides for optimal glass window aesthetics.

THERMALLY INSULATING Insulates and controls thermal energy loss from room to room and through glazing.

FIRE-RETARDANT The product is composed of a self-extinguishing, acrylic-impregnated foam, factory pre-coated with high-quality silicone.



DETAILS

MATERIAL Silicone with foam sealant

SIZE 1/2 inch to 6 inches

LENGTH 10 linear feet (3.04 meter)

APPLICATION Interior: Wall or Glass Surface Install

INSTALLATION Ceiling or Wall

COLORS Sikasil WS-295

MATERIALS



Silicone

MODELS - WALL

MODEL	JOINT SIZE at mean T° F	SEAL DEPTH
QTT-100	1" (25mm)	2" (50mm)
QTT-200	2" (50mm)	2" (50mm)
QTT-300	3" (75mm)	2" (50mm)
QTT-400	4" (100mm)	2" (50mm)
QTT-500	5" (125mm)	3" (75mm)
QTT-600	6" (150mm)	3" (75mm)

MODELS - GLAZING

MODEL	JOINT SIZE at mean T° F	SEAL DEPTH
QTG-100	1" (25mm)	2" (50mm)
QTG-200	2" (50mm)	2" (50mm)
QTG-300	3" (75mm)	2" (50mm)
QTG-400	4" (100mm)	2" (50mm)
QTG-500	5" (125mm)	3" (75mm)
QTG-600	6" (150mm)	3" (75mm)