
Fire Extinguishers

PRINCIPLES OF SELECTING EXTINGUISHERS:



TYPICAL STORED-PRESSURE FIRE EXTINGUISHER

- Type of potential fire hazard.
- · Severity of potential fire hazard.
- Environmental conditions of potential fire hazard.
- Effectiveness of extinguisher on potential fire hazard.
- Training and physical capabilities of available personnel to operate extinguisher.
- Upkeep and maintenance requirements of extinguisher.

For further information, refer to NFPA 10.

FIRE CLASSIFICATIONS						
TYPE OF FIRE	Wood, paper, cloth, trash & other ordinary combustibles	liquids	Energized electric equipment	appliances w/		
CLASS AND LETTER SYMBOL	A	В	0	K		
PICTURE SYMBOL						
AGENTS						
MULTI-PURPOSE DRY CHEMICAL	Yes	Yes	Yes	No		
KITCHEN	Yes	No	No	Yes		
WATER	Yes	No	No	No		
FFFP	Yes	Yes	No	No		
BC DRY CHEMICAL	No	Yes	Yes	No		
CARBON DIOXIDE	No	Yes	Yes	No		

ABC Dry Chemical

FIRE EXTINGUISHERS



The ABC Multi-Purpose Dry Chemical fire extinguisher is used to provide protection against Class A, B and C fires.

FINISH Glossy red polyester coated

MOUNTING Wall bracket **DISCHARGE** Nozzle or hose

AGENT BASE Ammonium Phosphate

PRESSURE 195 P.S.I.

HALOTRON 1

MOUNTING BRACKET

FITS SIZE
5 Lbs.
6 Lbs.
10 Lbs.
20 Lbs.
5, 6, 10 Lbs.
20 Lbs.

MODEL	NOMINAL CAPACITY	順 RATING	HEIGHT	CYLINDER DIAMETER	RANGE OF STREAM	TYPE DISCHARGE
EX-3002	2-1/2 Lbs.	1A:10B:C	14-3/4"	3"	9' - 15'	Nozzle
EX-3005	5 Lbs.	2A:10B:C	15-1/4"	4-1/4"	12' - 18'	Hose
EX-3005-3	5 Lbs.	3A:40B:C	15-1/4"	4-1/4"	12' - 18'	Hose
EX-3006	6 Lbs.	3A:40B:C	16"	5"	15' - 21'	Hose
EX-3010	10 Lbs.	4A:80B:C	20"	5"	15' - 21'	Hose
EX-3020	20 Lbs.	20A:120B:C	23-1/4"	7"	15' - 21'	Hose

Kitchen Class K

FIRE EXTINGUISHERS



The Kitchen Class K portable fire extinguishers discharge a fine mist and help prevent grease splash and re-flash while cooling appliances. These wet chemical extinguishers are the best restaurant kitchen appliance portable fire extinguishers available and provide protection against Class K fires.

FINISH Stainless Steel
MOUNTING Wall bracket
DISCHARGE Hose

AGENT Potassium Acetate Solution

MODEL	NOMINAL CAPACITY	(ll) RATING	HEIGHT	CYLINDER DIAMETER	RANGE OF STREAM	TYPE DISCHARGE
EX-3260	6 ltr.	2A:K	19"	7"	10' - 12'	Hose
	2-1/2 gal.	2A:K	24-1/2"	7"	10' - 12'	Hose

MOUNTING BRACKET

MODEL	FITS SIZE			
EX-3904	2-1/2 gal.			
*OPTION:				
-AF Anti-freeze charge				

Call for information on water mist "Clean Agent" and pressurized water/foam extinguishers.