



Coastal Zone

EXTERIOR ACCESS DOOR

Nystrom Coastal Zone Exterior Access Door is the industry's only high velocity and impact tested door. With a design pressure of +/- 80psf, this door is sure to withstand mother nature's toughest storms.

FEATURES

IMPACT, AIR + WIND PRESSURE TESTED Independent lab tested to TAS 201, 202 and 203 assures the best protection against the harshest elements.

TEMPERATURE CONTROL With 1.6 inches of closed cell polyurethane insulation, the Coastal Zone Exterior Door delivers a R-11 thermal value.

CUSTOM SIZES Available in 1/4 inch increments from 18 inches by 18 inches to 36 inches by 48 inches maximum.



DETAILS

DOOR 24 gauge Steel

FRAME 0.080 inch 6063-T5 Extruded Aluminum

SIZE

- Min: 18 inches by 18 inches
- Max: 36 inches by 48 inches

INSTALLATION Wall

FLANGE Exposed

HINGE Stainless Steel Continuous Piano

FINISH

- Door: Paint Grip Finish
- Frame: Mill

INSULATION 1.6 inch Polyurethane; R-11

GASKETING EPDM Self-Adhesive, Continuous

COMPLIANCE Florida Product Approval FL38739

FLANGES



1 inch Flange

LATCHES



Non-Locking Handle



Locking Handle

ORDER GUIDE

BASE	LATCH	WIDTH	X	LENGTH	OPTIONS
XT			X		- H
	A Non-Locking Handle L Locking Handle	Standard Sizes (W x L)			C Drip cap S Stainless Steel, Type 304
		18" x 18" 20" x 30" 24" x 24"		24" x 30" 24" x 36" 36" x 36"	

Rough opening is door size. Additional sizes available, call for more information.