



# Concealed

## HINGED ACCESS DOOR

Designed for both ceiling and wall applications, the GFR panel can be used anywhere a locked door is required but style is still of utmost importance. The seamless design of these access doors blend into the surrounding drywall for a clean, upscale appearance.

### FEATURES

**ECO FRIENDLY** These panels contain a 70% post-consumer recycled glass content for a truly GREEN product.

**OPTIONAL LOCKS** Constructed with european style hinges and choice of screwdriver cam latch or keyed cam lock.

**CORNER OPTIONS** Standard and custom sizes available in radius or square corners.

### DETAILS

**DOOR** Gypsum Fiber Reinforced

**FRAME** Gypsum Fiber Reinforced

**DOOR SHAPE** Radius Corner or Square Corner

#### SIZE

- Min: 6 inches by 6 inches
- Max: 30 inches by 30 inches

**INSTALLATION** Wall or Ceiling

**FLANGE** Drywall

**HINGE** European

**FINISH** Unfinished Gypsum, Natural Gypsum White

### FINISH



Natural Gypsum  
White

### DOOR SHAPE



Radius  
Corner




Square  
Corner

### LATCHES



Screwdriver  
Cam Latch



Keyed Cam  
Lock

### ORDER GUIDE

BASE	DOOR SHAPE	LATCH	WIDTH	X	LENGTH
GFR			—	X	
	R Radius Corner S Square Corner	C Screwdriver Cam Latch L Keyed Cam Lock	Standard Sizes (W x L) 8" x 8"    16" x 16"    24" x 24" 10" x 10"    18" x 18"    30" x 30" 12" x 12"    22" x 30"		

Rough opening is door size + 6 inches.

Additional sizes available, call for more information.