



Top Security ACCESS DOOR



Nystrom Top Security Access Door is manufactured with detention-grade materials and provides access through openings in walls. The pan style access door includes a heavy-duty butt hinge welded on the surface of the door to prevent unwanted access.

ORDER GUIDE

BASE	LATCH	WIDTH	X	LENGTH	OPTIONS
TS			X		
	D Detention Lock Prep M Mortise Lock (1 1/8 inch) Prep	Standard Sizes (W x L) 12" x 12" 22" x 30" 24" x 40" 16" x 16" 24" x 24" 24" x 48" 18" x 18" 24" x 36"*			G Gasketing M Masonry Anchors S Stainless Steel, Type 304

Rough opening is door size + 3/4 inch minimum.
 Additional sizes available, call for more information.
 *Recommended for Wall surfaces only.

DETAILS

- DOOR** 7 Gauge formed steel door
- FRAME** 3/16 inch steel angle - 2 inches by 3 inches
- SIZE**
 - Min: 8 inches by 8 inches
 - Max: 48 inches by 54 inches
- INSTALLATION** Ceiling or Wall
- FLANGE** 2" Exposed
- HINGE** Surface Mounted Heavy-Duty Butt
- PAN DEPTH** 1 1/4 inch
- FINISH** White Powder Primer Coat



Draft Stop ACCESS DOOR

Nystrom Draft Stop Door is a non-rated access door designed to provide access through wall openings of draft stop spaces in the attic while preventing a back draft from one section of the attic to another. This self-closing and self-latching access door allows for access from both sides of the door.

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
D				X		
	T 1 inch Flange W Drywall Bead	K Knurled Knob/Key Operated Latch Bolt M Mortise Lock (1 1/8 inch) Prep	Standard Sizes (W x L) 12" x 12" 22" x 30" 24" x 40" 16" x 16" 24" x 24" 24" x 48" 18" x 18" 24" x 36"*			B Galvannealed G Gasketing S Stainless Steel, Type 304

Rough opening is door size + 1/4 inch. Additional sizes available, call for more information.
 *Recommended for Wall surfaces only.

DETAILS

- DOOR** 14 gauge Steel (self-closing)
- FRAME** 16 gauge Steel
- SIZE**
 - Min: 6 inches by 6 inches
 - DT Max: 24 inches by 72 inches, 36 inches by 60 inches or 48 inches by 48 inches
 - DW Max: 36 inches by 48 inches
- INSTALLATION** Wall
- FLANGE** Exposed or Drywall Bead
- HINGE**
 - DT: Flush Continuous Piano
 - DW: Concealed Pin
- FINISH** White Powder Primer Coat