

ITEM NO. PART NUMBER QTY. DESCRIPTION 27496-10.50-Y 4 RAIL, 1-1/4" X 10.50L, 27496-18.00-Y 2 RAIL, 1-1/4" X 18.00L, 20 27496-60.50-Y 4 RAIL, 1-1/4" X 60.50L, 30 500 27180-A-Y 4 PKG, CORNER POST, ZPS, 27185 FTG, ELBOW, 510 6 515 27188 2 FTG, TEE, FTG, CROSS ELBOW, 520 27186 2 FTG, DBL TEE, 575 SRCAY-GATE-30 1 GATE, 30,

66.97 OVERALL 56.68 56.68 OVERALL

SPECIFICATIONS

D

RAILS, POSTS: 6061 T6 ALUMINUM ALLOY 1 /14" I.D. SCH 40

GATE: 1 1/4" TUBULAR ALUMINUM SELF CLOSING WITH COIL SPRING, ZINC PLATED

COUNTERFLASH MOUNTING BRACKETS: 3/16" ZINC PLATED STEEL FASTENED TO STEEL BACKING PLATE

BOLTS: HEX HEAD BOLTS 3/8"-16 x 3/4" GRADE 5 ZINC PLATED

RAILING FITTINGS AND PLUGS: MANUFACTURER'S STANDARD CAST WITH SET SCREW HOLD

FITS HATCH SIZES UP TO 48" X 48"

CERTIFICATIONS: MEETS OSHA 29 CFR 1910.23 GUARDING FOR OPENINGS REQUIREMENTS; SUPPORTS 200 LBS. FORCE

FINISH: SAFETY YELLOW POWDER COAT

SRBAY48X48FG

	9300 73rd Avenue North Minneapolis, MN 55428			TITLE: Safety Railings for Roof Hatch 48X48, Front Exit, Therm-Brokn Aluminum, Safety Yellow Pwd, Gate, 3" Curb				
		NAME	DATE	SIZE	DWG. NO.			REV
`	DRAWN	SJB	TODAY		SRBAY48X48FG		Α	
,.	RELEASED	DWO	1/4/2019		HT: Weight		SHEET 1 OF 1	
2					2		1	

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED. ©2020 NYSTROM, INC.

5

3