

5 WIDTH

SPECIFICATIONS:

 $\langle 1 \rangle$ DOOR:

STEEL 3/16" DIAMOND PLATE, GRAY PRIMER FINISH WITH A STEEL 3/16" DIAMOND PLATE, GRAY PRIMER FINISH WITH A LIVE LOAD OF 300 PSF WITH A MAX SPAN DEFLECTION OF 1/150

ANCHOR: 3/8" HOLES PROVIDED FOR BOLT IN ON SITE, ANCHORS PROVIDED BY OTHERS $\langle \overline{2} \rangle$ FRAME:

STEEL, 3/16" FORMED SMOOTH PLATE, GRAY PRIMER FINISH

(3) HINGES: TYPE 316 STAINLESS STEEL

⟨4⟩ SLAM LATCH:

TYPE 316 STAINLESS STEEL WITH INSIDE LEVER HANDLE AND

OUTSIDE REMOVABLE HANDLE (5) COUNTER-BALANCE SPRING:

ENCLOSED, TYPE 17-7 SST SPRING

(6) HOLD-OPEN ARM:

TYPE 316 STAINLESS STEEL WITH RED VINYL GRIP HANDLE

(7) DRAINAGE COUPLING: 1-1/2"

(8) FLUSH TYPE PLUG SEAL: TYPE 316 STAINLESS STEEL

FLOOR DOOR SIZE:

QTY: PART#: TITLE: Floor Door, Drainable Series, Sngl Dr, 316 SST Hdw, Steel, Prime Coat, Pedestrian, Bolt-In, Slam 9300 73rd Avenue North, Minneapolis, MN 55428 Latch Removbl L Hdl SIZE DWG. NO. REV NAME DATE Nystrom FD FDDPP_X_SWL-BI ShpDr Α DRAWN SWS 8/3/2018 RELEASED TR 8/3/2018 SHEET 1 OF 2 WEIGHT:

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

PROJECT:

ARCHITECT:

CONTRACTOR:



