







SPECIFICATIONS:

(1) DOOR: ALUMINUM, 1/4" DIAMOND PLATE, MILL FINISH WITH A H20 LOAD RATING FOR INFREQUENT LOW SPEED TRAFFIC WITH A MAXIMUM DEFLECTION OF L/160

- (2) **FRAME:** ALUMINUM, 1/4" EXTRUSION, EPOXY PAINT FINISH ON EXTERIOR SURFACES THAT COME IN CONTACT WITH CONCRETE
- (3) HINGES: TYPE 316 STAINLESS STEEL
- 4 SLAM LATCH: TYPE 316 STAINLESS STEEL WITH INSIDE LEVER HANDLE AND OUTSIDE REMOVABLE 5/16" SQUARE L HANDLE
- (5) COUNTER-BALANCE SPRING: TYPE 17-7 STAINLESS STEEL SPRING ENCLOSED IN A TYPE 316 STAINLESS STEEL TELESCOPING TUBE
- (6) HOLD-OPEN ARM: TYPE 316 STAINLESS STEEL
- (7) ANCHOR: 4" CONCRETE ANCHOR STRAPS PROVIDED

(8) FLUSH LIFTING HANDLE: TYPE 316 STAINLESS STEEL

FLOOR DOOR SIZE:

" (WIDTH) x " (LENGTH)

CLEAR UNOBSTRUCTED OPENING:

" (WIDTH) x " (LENGTH)

OPENING:

" (WIDTH) x " (LENGTH)

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED. THIS IS A GENERIC SHOP DRAWING AND MAY NOT BE AN ACTUAL REPRESENTATION OF THE FINAL PRODUCT.

PROJECT:									
ARCHITECT:									
CONTRACTOR:									
QTY:									
PART#:				FDNI	HA	Х	DAL		
▶ (nystrom ®				TITLE: Floor Door, Non-Drainable, Dbl Dr, 316 SST Hdw,					
9300 73rd Avenue North Minneapolis, MN 55428				Alum, Mill, H20, Cast-In Anchors, Slam Latch Removbl L Hdl					
	NAME	DATE	SIZE	DWG. NO.					REV
DRAWN	JE	04/18/11	Α		FD	NHA_X ₋	_DAL		Α

WEIGHT: Varies

SHEET 1 OF 2

RELEASED DWO 04/18/11

