

FRONT ELEVATION
NOT TO SCALE


SPECIFICATIONS

- 2" X 2" X 3/16" STEEL ANGLE FRAME
- 1" X 1" X 1/8" STEEL ANGLE DOOR STOP
- 10 GAUGE STEEL PLATE DOOR
- ALL EXPOSED JOINTS WELDED, FILLED AND GROUND SMOOTH
- WHITE BAKED ON POWDER COAT FINISH
- 4" X 4" BUTT HINGE WELDED TO DOOR AND FRAME
- PINNED ALLEN HEAD SECURITY SCREWS (STANDARD ON PANELS 24 X 24 AND LARGER)
- PREPARED TO MOUNT STANDARD DETENTION LOCK USING 5/16 - 18 X 1.75: FLAT HD PINNED TORX SECURITY SCREWS (SCREWS PROVIDED WHEN FACTORY FURNISHES LOCK)

OPTIONS

- ☐ PREPARATION FOR 1.125" MORTISE CYLINDER (CYLINDER PROVIDED BY OTHERS OR BY FACTORY)
- ☐ PREPARATION FOR HEAVY DUTY DETENTION DEAD-BOLT LOCK (LOCK PROVIDED BY OTHERS OR BY FACTORY)
- ☐ MASONRY ANCHORS ATTACHED

ROUGH OPENING: x



A
A CUT-THRU SECTION
NOT TO SCALE