Personnel™ II

ROOF HATCH

The Personnel II Roof Hatch is designed with OSHA life safety in mind and provides easy access to roof areas. Simple to install and operate, this roof hatch is OSHA Compliant, stays cooler and conserves energy.

FEATURES

GAS SPRING OPERATION Designed for smooth one-handed operation that complies with OSHA safety standards, this roof hatch is easy to open and close.

CLEAR LABELING Color coordinated labels clearly identify safety yellow pull down handle and red hold open arm release.

RAILING-READY Safety railings install quick and easy with predrilled counterflash, designed to meet the 42" height requirement per OSHA and IBC.



DETAILS

MATERIAL

- Aluminum: 11 gauge, mill
- Steel: Galvanneal 14 gauge, ANSI 70 Gray powder coat
- Stainless Steel: Type 304, 14 gauge, 2B matte finish

COVER Formed metal cover with liner, stiffened to withstand a live load of 40psf with a max deflection of 1/150 of the span

CURB Single wall curb with EZ tab counterflash and mounting flange

INSULATION 1 inch polystyrene in cover, 1 inch polyiso around curb or optional 2 inch polyiso in cover and curb; R-12, specify -IRR

GASKET Extruded EPDM adhesive backed gasket seal, continuous around cover

SPRING Gas spring with integrated damper for smooth, controlled lift assistance

HINGE Heavy-duty pintle hinge with stainless steel hinge pin

HOLD OPEN ARM Zinc plated steel automatic hold open arm with red vinyl grip handle locks cover in open position

LATCH Zinc plated steel slam latch with exterior and interior turn handle and padlock hasps; 20psf wind uplift for lengths ≤ 60 inches.

PULL HANDLE Interior safety pull down handle, yellow powder coat

STANDARD MODELS

GRAY	WHITE	ALUMINUM	SIZE (IN.)	ACCESS
G3630	W3630	A3630	36 x 30	Ladder
G3636	W3636	A3636	36 x 36	Ladder
G4848	W4848	A4848	48 x 48	Ladder
G3054	W3054	A3054	30 x 54	Ship Stair

Additional sizes and options available, call for more information.

FINISHES



Aluminum



Powder Coat

High Reflectance

White Powder



2B Matte Stainless Steel

